

ELECTRIC PATTERN
SEWING MACHINE

电脑花样机

完全根据缝纫数据进行精准缝纫
强大的机针贯穿力
直接驱动、耗电低
定位简单准确的二步压脚

Exactly accurate stitch basis on sewing data.
Powerful needle penetration.
Direct drive ,lower power consumptive.
Easy location and accurate 2 steps of presser.



CC-6040G-01A

缝制范围：600x400mm

宽大的缝制区域实现多样化缝纫，可同时缝制鞋类和衣物的多个小物件的组合缝纫，同时也可以缝纫皮包和汽车内饰及安全气囊等大的缝制物品。搭载550W伺服电机，强大的机针贯穿力在低速时厚料也能缝出精美的线迹。

More large stitching area can sew more kinds of sewing samples, which can sewing shoes or clothing, which have been included of many small parts in one product. At the same time ,which can sewing leather bag and car's inside decorative products,with 550 W servo motor,stronger needle penetration can sew beautiful line tracks for heavy material at low sewing speed.



规格 Specification

型号Model	CC-6040G-01A
线迹型式Line	单针平缝Single-needle flat seam
最高缝纫速度Highest sewing speed	2,700 rpm
缝制区域(X × Y) Sewing area	600×400 mm
送布装置 Cloth feeding device	间歇送布 (脉冲马达驱动) Intermittent feeding (driven by pulse motor)
针距 Stitch length	0.05 - 12.7mm
最大针数 Max. needle number	20,000针/1个图案(20,000 needles/1 pattern)
压脚驱动方式 Foot presser driving mode	气动 Pneumatic
压脚高度 Work Clamp Height	最大Max. 30 mm
两步压脚 2-step presser foot	一体式压脚 All-in-one presser foot
间歇压脚上升量 Rising amount of intermittent foot presser	22 mm
间歇压脚行程 Stroke by intermittent presser foot	0或2 - 10 mm (出厂设置: 3mm) 0 or 2 - 10 mm (Factory defaults: 3mm)
旋梭 Hook	两倍摆梭 Double Shuttle Hook
扫线装置 Scavenging device	标准装备 Standard facility
切线装置 Cutting device	标准装备 Standard facility
夹线器 Tension device	电子夹线器 Electric tension device
数据存储方式 Data storage way	USB或闪存 (使用CF卡可任意缝纫图案) USB or Flash memory (You can sew pattern with CF card)
马达 Motor	AC伺服马达550W AC servomotor 550W
重量 Weight	机头: 约160 kg 操作盘: 约0.6 kg 控制箱: 14.2 - 16.2 kg Head: about 160 kg Operating panel: about 0.6 kg control box: 14.2 - 16.2 kg (according to different export countries)
电源 Power	单相220V Single phase 220V 三相 Three-phase 380V
气压 Air pressure	0.5 Mpa 1.8 L/min
净重/N.W	500
毛重/G.W	570
包装尺寸/Measurement	1710*1640*1400
体积/CBM	3.9m ³